

Electronic Cable

UL STYLE NO.20276





UL File No.-----E205596

Standard-----UL Subject 758

Use-----Internal Wiring of external interconnection of electronic equipment in class 2 circuits only

Rating-----

STYLE NO.	Volt (max.)	Temp.(max.)
UL STYLE NO.20276	30V	80°C

Sectional Construction	Conductor Wire Size (AWG)	P.P Ins Diam (mm)	PVC Jacket Diam (mm)	Production Description
	7/0.10 30AWG	0.59	5.85	1 pair of 28AWG and 9 pairs of 30AWG, PP insulated. overall AL-PET foil plus 90% Min. tinned copper braid shield .PVC Jacket.
	7/0.12 28AWG			
	7/0.10 30AWG	0.59	6.20	1 pair of 28AWG and 12 pairs of 30AWG, PP insulated. overall AL-PET foil plus 90% Min. tinned copper braid shield .PVC Jacket.
	7/0.12 28AWG			
	7/0.10 30AWG	0.59	8.00	1 pair of 28AWG and 24 pairs of 30AWG, PP insulated. overall AL-PET foil plus 90% Min. tinned copper braid shield .PVC Jacket.
	7/0.12 28AWG			
	7/0.10 30AWG	0.59	9.0	2 pair of 28AWG and 32 pairs of 30AWG, PP insulated. overall AL-PET foil plus 90% Min. tinned copper braid shield .PVC Jacket.
	7/0.12 28AWG			